



Millenium Color Multiplexers

Full Duplex

MODEL MTI - 9CD




Plus These Outstanding Advantages ...

- Color High Resolution Display and Recording.
NTSC 858 x 525 (pixels x lines) maximum
PAL 864 x 626 (pixels x lines) maximum
- Multi Image Display 1, 4, and 9 pictures on screen.
- Rugged Metal Case approx. 1.5U Height.
- Full Duplex Operation for simultaneous recording and live multi-image monitor or VCR playback.
- True Video Motion Detection for Outdoor Applications with 3 Motion Parameters for alarming on unwanted movement.
Object Size
Sensitivity
262,144 Detection Points with 288 Programmable Zones
Night / Day Mode and Three Daily On / Off Timers
- Simultaneous Video Activity Detection with sensitivity settings for increasing the camera update rate when movement in any camera is present.
- 9 Alarm Inputs either NO or NC
- Alarm Output NO or NC
- Interactive On - Screen Programming Password Protected
- Auto Configure for PAL or NTSC
- Power Input Voltage Free 100 - 240 VAC 50/60 Hz
- Printer Port for Alarm Log
- Windows Software include for control and programming
- Compatible with Standard VHS or SVHS VCRs
- 2X Zoom with Screen Pan Tilt function
- 3 Monitor Outputs 1 Main Monitor and 2 Analog Call Monitors


- Programmable Sequences for Analog monitors
- Four Daily Sequence Timers and Multi OSD Language Support
- Video loss Display and Alarm
- Audible and Visual Alarm Responses
- VCR Switcher Pulse Compatible
- 4 Digit Password Protection.
- Remote Keyboard Optional




9/16 Channel Recording and Display



Multi-image & Dual Call Monitors



Auto Switching on Call Monitors



Multi-image Alarm Display & Printout



“Always Working to Make Things Better”
A.V.E. (Thailand) Co., Ltd.
217/4 Crystal Garden, Soi 4, Sukhumvit Rd.,
Klongtoey, Klongtoey, BKK. 10110
Tel: (662) 6568231~2 Fax: (662) 6569554
email : ave@avethailand.com
web site : www.avethailand.com



Designed for use in today's most demanding CCTV surveillance applications, this color, Full duplex video multiplexer features an advanced digital image processing system which allows for simultaneous recording, playback and display of up to nine video inputs on the MTI - 9CD onto a video recorder and monitor. This system, unlike "quad" image processors records only full size images to insure that there is no loss of quality during full-screen image playback.

Main monitor live video input and tape playback display formats include sequentially switched full-screen images, four sequentially switched 2X2 image displays, two sequentially switched and 3X3 image displays. 2X zoom of full-screen images is also available in the live display. All displays include the time, date and 20 character video input titles.

A programmable alarm management and reporting system make these multiplexers perfect for unattended monitoring application. This system combines built-in Video Activity Detection (VAD) and Video Motion Detection (VMD) with hard wired alarm inputs (WAI) for total flexibility in alarm management. Individual alarm channel setup options include:

Weekly Format : Mon-Sun, or Mon-Fri and Sat-Sun
Daily Format : Day and night, three on/off times
Detection : Off, VMD, WAI, VMD & WAI
VAD/VMD : Object size, sensitivity and tracking

One, four, nine or sixteen images of each alarm event may be stored to memory at 1 second intervals. These images and the log generated by up to 100 alarm events may be displayed on-screen or can be downloaded to a PC.

Two "call" monitor outputs (A and B) are provided for detailed, full-screen image viewing. For normal mode viewing, each output may be assigned four pre-programmed, timer controlled switching sequences. Single images may be manually called to each output. Alarm generated images are displayed on call monitor A.

TECHNICAL SPECIFICATIONS

Television Standards	Auto Detect: NTSC, EIA, CCIR, PAL
Power Standards	Auto Detect: 100 - 240 VAC; 50/60 Hz
Resolution (pixels x lines)	NTSC 858 x 525 Maximum NTSC 720 x 480 Normal Monitor Display PAL 864 x 625 Maximum PAL 720 x 576 Normal Monitor Display
Video Inputs	9 : 1V p-p, Composite, Video BNC, Looping
Termination Selection	Each Channel via Dipswitch: HI-Z or 75 ohm Terminated
Video Monitor Outputs	3 : 1V p-p, Composite Video BNC
Main Monitor Display	Full Screen, 3x3, 2x2 or 2x Zoomed
VCR Video Inputs	1 : 1V P-P Composite, 75 ohms BNC 1 : SVHS Component Y/C Input
VCR Video Outputs	1 : 1V P-P Composite, 75 ohms BNC 1 : SVHS Component Y/C Output
VCR Control Input	Camera Switcher or VCR Gate Pulse
Call Monitor Displays	2 : Manual, Sequenced or Homed Full Screen Image 4 timed Switching Sequences per day Mon-Sun or Mon-Fri and Sat-Sun
Frame Rate Control	3 Timers per day for changing switching speeds : Mon-Sun, or Mon-Fri and Sat-Sun
Information Displays	Time, Date, 20 Character Titles, setup menus, alarm log and alarm images.

Time Date Format	Universal Format Selection 12 hr or 24 hr clock MM/ DD/ YR, DD/ MM/ YR or YR/ MM/ DD
Screen Languages	English, French, German
Wired Alarm Inputs	9 : 1 Amp @ 30 V, NO or NC
Wired Alarm Outputs	1 : NO or NC Programmable Wired and/or VMD Alarms.
Alarm Indication	Audible and/or Visual
Alarm Duration Time	Up to 4 minutes per alarm input.
Video Loss Alarm	"Video Loss" display and audible alert
Alarm Images	1, 4, 9 or 16 may be stored at on 1 second intervals, displayed or printed as multi-images.
Alarm Reports	On-screen or printed: channel number, time, date, or auto print every 24 hours
Video Motion Detection (VMD)	262,144 detection points per camera, 3 Motion Detection Parameters, 24H x 12V (288) Programmable zones Object size, Sensitivity. 3 Daily Timers per camera for ON/ OFF times, Mon-Sun, or Mon-Fri & Sat-Sun, Day / Night Timer for all cameras
Video Activity Detection (VAD)	24H x 12V (288) Programmable zones Sensitivity Setting per camera
Setup Programming	On-screen menus via keyboard or computer download.
RS232 Serial Port	Remote Keyboard or computer download and/ or control
Centronics Printer Port	Alarm Report printing
Security	Four digit Password Protection
Data Port	Optional DB9
Operating Temperature	40-104 degrees F or 5-40 degrees C
Dimensions	(H 57 mm x W 310 mm x D 312 mm)
Rack Mounting	Standard 19" rack, 2U
Weight	7.7 lbs (3.5 kg)
Color	Grey case beige Front
Shipping Box Size	450 mm x 560 mm x 110 mm
Shipping Box Weight	8.8 lbs (4.0 kg)
Options	Remote keyboard RS-232

AVE Thailand Co., LTD.
Crystal Garden
217/04 Sukhumvit Soi 4 NanaTai
Klongtoey, Klongtoey, Bangkok, 10110
Tel 662 656 8231- 8232
Fax 662 656 9554
ave@avethailand.com